

www.kleemannlifts.com
www.kleemannlifts.cn



This is the ordinary publication. Printed content is for reference only, subject to change without notice. KLEEMANN reserves the sole right of interpretation of this brochure.

本书为一般信息类出版物，图片仅供参考。KLEEMANN有权在未事先通知的情况下进行更改。
KLEEMANN保留对本样册的唯一解释权。

Copyright © KLEEMANN 2024

KLEEMANN Lifts(China)Co. Ltd.
Address: No.100 DengTa Road,
KSND, Jiangsu, China
Post code: 215316
Tel: +86 512 3682 3223

科莱曼电梯(中国)有限公司
地址: 中国昆山高新区灯塔路100号
邮编: 215316
电话: 0512 36823223



chn-products-maison_tp-encn- 20240402



MAISON TP平台电梯
MAISON TP Home Lifts



A Starting Point 出发点

是什么使得科莱曼家用电梯解决方案制造身份如此可信？

这是我们的起源，一个宇宙来源的永恒灵感。在科莱曼我们长期致力于设计和建造家用电梯解决方案，几乎很容易就辨认出它身上的希腊文化，当然也有您的独特需求。美学，这在希腊哲学中意味着认知、感受、欣赏以及重建自然的美丽和真实，是我们的出发点。

What makes KLEEMANN home solutions manufacturing identity so trustworthy?

It is our origins, a universal source of eternal inspiration. At KLEEMANN, our goal has been to design and construct home solutions almost as distinguishable as Greek culture and, of course, as unique as your needs are. Aesthetics, which in Greek philosophy means to perceive, feel, appreciate, and recreate the beauty and truth of nature, is our starting point.

Company Profile 公司介绍

KLEEMANN起源于德国的KLEEMANN HUBTECHNIK GmbH公司。

目前科莱曼集团在全球十多个国家设立子公司，产品和服务遍及全球100多个国家。

KLEEMANN originated from KLEEMANN HUBTECHNIK GmbH in Germany.

At present the KLEEMANN Group has established subsidiaries in more than ten countries around the world and its products and services are available in more than 100 countries worldwide.

1983年 The 1983 Year

通过技术引进和转让，在希腊成立科莱曼集团总部。

Establishment of the headquarters of the Clayman Group in Greece through technology introduction and transfer.

2011年 The 2011 Year

KLEEMANN被世界电梯杂志评为是全球七大电梯供应商之一，也是全球领先的液压电梯制造商和船梯制造商。

KLEEMANN has been recognized as one of the 7 major elevator companies in the world by Elevator World Magazine.

2011年 The 2011 Year

KLEEMANN在中国昆山全资成立了科莱曼电梯(中国)有限公司，为中国、远东和太平洋地区提供产品和服务。

KLEEMANN established a wholly owned KLEEMANN Elevator (China) Co., Ltd. in Kunshan, China to provide products and services to China, the Far East and the Pacific.

2015年 The 2015 Year

科莱曼集团和昆山高新区政府达成协议，追加包括新的高标准生产车间和测试塔等项目。这一投资也是希腊企业在中国最大的投资之一。

KLEEMANN Group decided to invest another 15 million US dollars to build new assembly lines in Kunshan.

2019年 The 2019 Year

KLEEMANN在中国昆山新工厂完工启用，新工厂具有完全符合欧洲标准的100米高且极富设计感的测试塔。

KLEEMANN opens its new plant in Kunshan, China, with a 100-meter-high, design-oriented test tower that fully complies with European standards.



舒适生活
Comfortable



安全保障
Safety



智能控制
Intelligence



专属定制
Customized
Service

Feel The Design 感受我们的设计

A Whole New Life Experience 一个全新的提升体验

在科莱曼，电梯不仅仅是一个上下移动的长方形盒子，我们考虑您的体验感受，为您提供与众不同的舒适提升体验。

Rather than thinking of the elevator as a box, KLEEMANN Design thinks of it as a unique space in the building and transforms the whole elevator experience into a new value for the people, the building, and the environment.

科莱曼客户服务热线
24/7 Support
400-0900-981

Tranquil Moment 静享舒适好时光

采用永磁同步钢带曳引驱动

Permanent Magnet Synchronous Motor w. Belt

永磁同步驱动与数字变频技术结合, 更加高效节能

High efficiency and energy-saving with digital variable-frequency technology

不需要添加润滑, 无污染

Non lubricating oil, non-polluting.

扁平钢带更柔韧, 降低了运行噪音

Flat ropes, more flexible, and low noises

超薄静音控制柜

Silent & Ultra-thin Controller

采用无接触器技术, 运行声音低于 52 dB, 运行更安静

Solution without contractors, operate more quietly (below 52dB)

超薄的控制柜, 布置随心所欲

Small size controller (770mmH*470mmW*220mmD), flexible installation location

Safety First 以人为本 安全安心



ARD系统 ARD System

标配应急电源, 保证电梯意外断电后就近平层放人

Equipped ARD as standard, emergency leveling when power-off.



一键呼救系统 Emergency Call

当电梯出现故障, 可在轿内直接拨打预设的5组电话 (5G 三网通), 保证家人的安全

Call the present phone numbers (5 contacts) by clicking the emergency button during power-off.



厅门防夹保护 Anti-pinch Protection From Landing Door

厅门开闭过程种, 如遇阻挡, 厅门自动反向动作, 保证设备与乘客安全

In the process of opening and closing, the landing door will automatically reverse whenever the soothing is blocked.



平台红外线安全保护 Infrared Safety Protection

保护装置对进入其探测区域的物体进行扫描, 一旦光线受到干扰, 电梯门将重新开启而不会碰伤乘客, 保障乘客安全

The protection device scans the objects entering its detection area. Once the light is disturbed, the elevator door will reopen without hurting passengers, to ensure the safety of passengers.



Intelligence Interaction 智能交互 触手可及

智能物联网 (选配) Smart IOT (optional)

24h全天候智能监测电梯安全运行
Operating status monitoring within 24hrs
Operating status monitoring within 24hrs
系统根据设置自动检测电梯运行状态, 对电梯维保、故障进行预防性提醒
The system automatically detects the operation status and sends elevator maintenance and fault codes in advance according to the settings

智能人机界面Intelligence HMI

智能触屏控制
Touch-sensitive
友好的人机互动界面
Human-friendly HMI

Customized Service 灵动无限 专属定制

可3面开门,合理户内设计布局,匹配各种户型

Three side open options, match all kinds of house types

根据客户现场,以10mm为单位定制平台,最大限度的利用每一寸空间

Customized platform according to project adjusted by each 10mm, more efficient use of space

个性化设计风格的壁板、吊顶、地板,自由搭配,实现您私人定制的想法

Design your lifts, by choosing your favorite background panel, ceiling, floors, etc.

Basic Parameters 基本参数

驱动方式 Machine	永磁同步无齿轮钢带曳引驱动 Permanent magnet synchronous motor with belt
载重 Load	250kg/320kg/400kg
速度 Speed	0.3 m/s
行程 Travel	2300mm-15000mm
层站 Stops	2层2站—6层6站 2Floors —6Floors
最小顶层高度 Min Headroom	2400mm
最小底坑深度 Min Pit Depth	100mm
框架宽度 Frame Width	850 mm-1300 mm
框架深度 Frame Depth	950 mm-1500 mm
开门方式 Door Type	自动中分双扇外开门/单扇手拉门 Auto-CO Swing Door/Handle Single Door
开门类型 Open Type	同侧开门/贯通开门/直角开门/三侧开门 Same side/Through/Right angled/Three sides
平台高度 Height of Platform	2000mm

Interface 人机界面



语音报站
Voice Announcement



实时显示电梯状态
Elevator Status Tracking



对外通话
External Phone Call



玻璃面板
Glass Panel



视频播放
Video Player



显示运行方向
Display Direction



显示层站位置
Display Cabin Location



按钮双色显示效果
Two-color display button



铝合金外框
Aluminum Alloy Frame

Door Opening Style
开门方式



自动中分双扇外开门
Auto-CO Swing Door



单扇手拉门
Handle Single Door

Controller
控制柜



一体化控制柜Integrated controller
选配 (Optional)



Atmosphere Lamp
氛围灯



Yellow
黄色灯带



White
白色灯带



Blue
蓝色灯带

Ceiling Selection
井道吊顶选择



C201(标配Standard)



C202(标配Standard)



C301(选配Optional)



C101(标配Standard)



C102(标配Standard)

Platform HMI
平台人机界面



13.3“触摸屏 (标配)
Touch Sensitive
(Standard)

KCH-P13 (标配)



18.5“触摸屏 (选配)
Touch Sensitive
(Optional)

KCH-P18 H



LCH-P
(标配Standard)



感应式外呼 (选配)
Blueline (Optional)

Railing Selection
扶手选择



H101
(标配Standard)



H102
(标配Standard)



H103
(标配Standard)

Wall Panel Selection
壁板选择



BW101



BW104



BW102



BW105

Canbin & Platform
轿厢/平台



轿厢
Canbin BW103



平台
Platform BW103

Ceiling Selection
轿厢吊顶选择



D101(标配Standard)



D201(选配Optional)



D102(标配Standard)



D103(标配Standard)

Floor Selection
地板选择



地毯Carpet
(标配Standard)
FC101



地毯Carpet
(标配Standard)
FC102



地毯Carpet
(标配Standard)
FC103



PVC
(选配Optional)
FP201




PVC
(选配Optional)
FP202




PVC
(选配Optional)
FP203

Aluminum Alloy Frame Color 铝合金框架颜色



纯白 (KLSH08)
Pure White



银白 (KLSH07)
Silvery White



珍珠灰砂 (KLSH01)
Champagne Gold



黑砂闪银 (KLSH05)
Peral Matte Grey



香槟金 (KLSH06)
Glittering Black



时尚红 (KLSH09)
Trendy Red

所有铝合金井道及部件都采用6061高强度工业用铝，保证电梯的使用寿命和安全。
All aluminum shafts and components are made of 6061 high-strength industrial aluminum, ensuring the service life and safety of the elevator.

Dimension 尺寸

平台尺寸 Platform Dimension (mm)		框架外尺寸 Frame Outside Dimension(mm)		土建尺寸 Shaft Dimension (mm)		开门方式 Door Opening Type	开门宽度 Door Opening Width (mm)
PW	PD	SW	SD	TW	TD		
765	567	850	950	880	980	单扇手拉门 Handle Single Door	600
915	817	1000	1200	1030	1230	自动中分门 Automatic CO	710
1065	967	1150	1350	1180	1380	自动中分门 Automatic CO	860
1215	1117	1300	1500	1330	1530	自动中分门 Automatic CO	900

这里的尺寸只是标准产品的尺寸, 所有井道的布局图都请联系您的销售。
The dimensions here are only for standard products. Please contact your sales representative for the layout drawings of all shafts.

